

## **CP Application Instructions**

Apply CreteDefender CP by spraying or rolling onto clean, dry exterior concrete. Saturate the surface at a rate of 120 square feet per gallon (2.9 square meters per liter). You are not applying a membrane or coating. Only one application is required. Apply in generous quantities with single, overlapping passes. Any puddles or ponding should be removed from the concrete using a stiff broom or squeegee, moving the CP until there is none left standing on the surface of the concrete. Some areas may begin to dry before others. Do not re-apply CP to those areas, as they will turn a darker hue than the surrounding concrete. Treated areas are safe to use as soon as the product has dried.

All sealers and coatings, if any, must be removed from the surface in order for CreteDefender CP to be properly applied. Concrete more than 6 months old, or that has any dirt, grime or other substance blocking the pores at the surface must be removed prior to application.

CreteDefender CP is shipped in ready-to-use form. **DO NOT DILUTE.** CreteDefender CP is highly alkaline (pH 11-12) and protective eye wear (face shield recommended) and clothing must be worn when applying. Avoid contact with aluminum and glass. Coatings or paints cannot be applied over surfaces treated with CreteDefender CP. No sheen is created on the treated surfaces.

CreteDefender CP must not be applied if rain is expected within 24 hours of application. Do not allow water to contact a treated surface for 24 hours after application. If water contacts the treated surface before 24 hours have elapsed, you may need to re-apply CreteDefender CP.

Warranty: CreteDefender MS2 carries a 10 year limited product warranty.

CreteDefender, Inc. 1113 Tusculum Blvd, Suite 103, Greeneville, TN 37745 (877) 830-6008 [www.cretedefender.com](http://www.cretedefender.com)